

# General Wood Instructions

## Sanding

The rule of sanding is "Never across the grain".

1. Do not tear sandpaper. If you do, the ragged edges will often scratch the wood surface.
2. For flat surfaces, wrap a piece of sandpaper around a block of wood or use a store bought holder. Start with a coarse grade of paper and finish with a fine grade of paper(not included).
3. Be consistent. Do not sand one area with fine and another with coarse grade.

## Staining

1. Be sure the wood surface is smooth and clean. Stains can accentuate any roughness or scratches of cross grain sanding. Wipe off any dirt or dust with a soft cloth.
2. A base coat of sealer/primer and a light sanding before applying stain will insure a uniform stain.
3. Apply stains in one direction following the wood grain. Use a soft brush or foam brush. Let the stain penetrate the wood, then wipe off excess stain with a soft cloth.
4. If stain looks too dark, dampen the cloth with water/thinner and wipe until you achieve the desired color. If stain is too light, let dry, then apply another coat of stain and wipe off.

## Finishes

1. Outdoor projects may be finished with polyurethane or varnish.

**These are toxic and must be used in a well ventilated area.** Indoor projects may be finished with decoupage or left unfinished.

## Safety First!

This Product May Contain Silicon Gel Packets.  
**REMOVE PRIOR TO USE!**

**Three-Legged Stool Item# WD625**

**S&S**Worldwide

**CALL TOLL-FREE 1-800-243-9232**

or **Mail Your Order** to: S&S Worldwide  
PO Box 513

Colchester, CT 06415-0513

FAX #: 1-800-566-6678

Customer Service: 1-800-937-3482

Internet home page address: <http://www.ssworld.com>

Email address: [service@ssww.com](mailto:service@ssww.com)

Item No. WD625

Made in China

## Three-Legged Stool

**PLEASE READ ALL INSTRUCTIONS BEFORE STARTING**



- ☒ Precut Round Wooden Seat
- ☒ Wooden Dowels (Legs)
- ☒ Sandpaper
- ☒ Instructions

**YOU WILL NEED...**



Soft Cloth  
Paint or Stain  
Wood Glue  
Brushes

Protected Work Surface

**PREP TIME: 5 MIN**

**PROJECT TIME: 30 MIN**



### WARNING:

**CHOKING HAZARD** - Small parts. Not intended for children under 3 years.

**SUFFOCATION HAZARD** - To avoid danger of suffocation, keep plastic bags away from babies and children. Do not use bags in cribs, carriages, or playpens.

**S&S**Worldwide



## Product Instructions:

- a. Sand all wood parts until smooth.
- b. Wipe off excess dust with a soft cloth. It may be best to paint or stain pieces before assembling.
- c. Let dry 30 minutes.
- a. Test dowel legs to see that they fit snugly into holes beneath the round seat. If dowels seem too large, you may sand lightly until they fit easily.
- b. Put a small amount of glue into holes of round seat and insert legs.
- c. Cover bottom of legs with cloth and tap gently using a hammer.
- d. Let dry for approximately 30 minutes.
- **Wood Finishing:**
  - a. Create a rustic look by leaving assembled wood project unfinished.
  - b. Create a shiny protective finish over stain or paint by applying a coat of non-toxic decoupage finish. This works well for indoor projects.
  - c. If stool is to be subjected to outdoor weather, we recommend you use a polyurethane finish in a glossy or matte finish.



Log on to **www.ssw.com** for paint, stain, decoupage, brushes and other decorating supplies!

