

SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	Falcon Signal Horn
Other means of identification	FSH1, FSH1V, FSH1BU, FSH, FSHR
Recommended use	Produces loud sound. Signal Horn
Recommended restrictions	None known.
Manufacturer information	Falcon Safety Products, Inc. 25 Imclone Drive Branchburg, NJ 08876 US Phone: 1-908-707-4900 Emergency Phone: 1-800-498-7192
Supplier	See above.

2. Hazards Identification

Physical hazards	Flammable gases Gases under pressure	Category 1 Liquefied gas
Health hazards	Not classified.	
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	

Label elements



Signal word	Danger
Hazard statement	Extremely flammable gas. Contains gas under pressure; may explode if heated.
Precautionary statement	
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Response	Leaking gas fire: Do not extinguish, unless leak can be stopped safely. In case of leakage, eliminate all ignition sources.
Storage	Store in a well-ventilated place. Protect from sunlight. Store in a well-ventilated place.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Isobutane		75-28-5	100

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First Aid Measures

Inhalation	If symptoms develop, move person to fresh air. If symptoms persist, obtain medical attention. Intentional misuse by deliberately concentrating and inhaling aerosol products may be harmful or fatal.
-------------------	---

Skin contact	In case of contact with liquefied gas, thaw frosted parts with lukewarm water. Remove contaminated clothing. Treat for frostbite by gently warming affected area. Wash with soap and water. Obtain medical attention if irritation persists.
Eye contact	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
Ingestion	Not likely, due to the form of the product.
Most important symptoms/effects, acute and delayed	Contact with liquefied gas might cause frostbites, in some cases with tissue damage.
Indication of immediate medical attention and special treatment needed	Treat patient symptomatically. Treat frost-bitten areas as needed.
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media	Foam. Dry chemical powder.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters should wear full protective clothing including self- contained breathing apparatus.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED. In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Do not direct water at source of leak or safety devices as icing may occur. Use water spray to cool unopened containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Cool containers exposed to flames with water until well after the fire is out.
General fire hazards	Extremely flammable gas. Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling	Use good industrial hygiene practices in handling this material. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. All equipment used when handling the product must be grounded. Provide adequate ventilation. Avoid prolonged exposure. Wash thoroughly after handling. When using do not eat or drink.
--------------------------------------	--

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Protect from direct sunlight.
 Do not store at temperatures above 49 °C (120.2°F).
 Keep away from heat, sparks and open flame.
 This material can accumulate static charge which may cause spark and become an ignition source.
 Prevent electrostatic charge build-up by using common bonding and grounding techniques.
 Store away from incompatible materials (see Section 10 of the SDS).
 Stored containers should be periodically checked for general condition and leakage.
 Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value
Isobutane (CAS 75-28-5)	TWA	1000 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Isobutane (CAS 75-28-5)	STEL	1000 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Isobutane (CAS 75-28-5)	TWA	800 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Isobutane (CAS 75-28-5)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Isobutane (CAS 75-28-5)	TWA	1900 mg/m3 800 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields.

Skin protection

Hand protection

Wear protective gloves. Confirm with a reputable supplier first.

Other

Wear suitable protective clothing. As required by employer code.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.
 Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards

Not applicable.

General hygiene considerations

Use good industrial hygiene practices in handling this material. When using, do not eat, drink or smoke.

9. Physical and Chemical Properties

Appearance	Aerosol
Physical state	Gas.
Form	Liquefied gas.
Color	Colorless
Odor	Slight ethereal.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	10.94 °F (-11.7 °C)

Pour point	Not available.
Specific gravity	0.523
Partition coefficient (n-octanol/water)	Not available.
Flash point	-117.0 °F (-82.8 °C) Open Cup
Evaporation rate	> 1 (Ethyl Ether = 1.0)
Flammability (solid, gas)	Flammable gas.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)	1.8
Explosive limit - upper (%)	8.4
Vapor pressure	300 kPa
Vapor density	2.006
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	860 °F (460 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.59 lb/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and Reactivity

Reactivity	This may react with strong oxidizing agents.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Heat, open flames, static discharge, sparks and other ignition sources. Aerosol containers are unstable at temperatures above 49°C (120.2°F).
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Routes of exposure	Eye, Skin contact, Inhalation.
Information on likely routes of exposure	
Ingestion	Expected to be a low ingestion hazard. May cause stomach distress, nausea or vomiting.
Inhalation	Prolonged inhalation may be harmful. Excessive intentional inhalation may cause respiratory tract irritation and central nervous system effects (headache, dizziness).
Skin contact	Contact with liquefied gas might cause frostbites, in some cases with tissue damage.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Isobutane (CAS 75-28-5)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Mouse	1237 mg/L, 120 min, ECHA 57 %, 120 minutes, ECHA 52 mg/L, 1 h, HSDB

Components	Species	Test Results
		52 %, 120 min, ECHA
	Rat	> 80000 ppm, 10 min, ECHA
		1355 mg/L, 10 min, ECHA
		658 mg/l/4h, LOLI
Oral LD50	Not available	
Skin corrosion/irritation	Contact with liquefied gas might cause frostbites, in some cases with tissue damage.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	Non-hazardous by WHMIS/OSHA criteria.	
Carcinogenicity	See below.	
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects. Non-hazardous by WHMIS/OSHA criteria.	
Teratogenicity	Non-hazardous by WHMIS/OSHA criteria.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not likely, due to the form of the product.	
Chronic effects	Prolonged inhalation may be harmful.	

12. Ecological Information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	
Mobility in soil	
Mobility in general	No data available. Not available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue.

U.S. Department of Transportation (DOT)

Basic shipping requirements:

UN number	UN1075
Proper shipping name	Petroleum gases, liquefied
Hazard class	2.1
Special provisions	T50, N95
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	314, 315

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number	UN1075
Proper shipping name	LIQUEFIED PETROLEUM GASES
Hazard class	2.1

15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada DSL Challenge Substances: Listed substance

Isobutane (CAS 75-28-5)	Listed.
-------------------------	---------

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Isobutane (CAS 75-28-5)	1 TONNES
-------------------------	----------

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions This is consumer product and exempt from WHMIS regulation.

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Isobutane (CAS 75-28-5)	Listed.
-------------------------	---------

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
 Delayed Hazard - No
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)
 Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Isobutane (CAS 75-28-5)

US state regulations See below

US - Illinois Chemical Safety Act: Listed substance

Isobutane (CAS 75-28-5)

US - Louisiana Spill Reporting: Listed substance

Isobutane (CAS 75-28-5) Listed.

US - Minnesota Haz Subs: Listed substance

Isobutane (CAS 75-28-5) Listed.

US - New Jersey RTK - Substances: Listed substance

Isobutane (CAS 75-28-5)

US - Texas Effects Screening Levels: Listed substance

Isobutane (CAS 75-28-5) Listed.

US. Massachusetts RTK - Substance List

Isobutane (CAS 75-28-5)

US. New Jersey Worker and Community Right-to-Know Act

Isobutane (CAS 75-28-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Isobutane (CAS 75-28-5)

US. Rhode Island RTK

Isobutane (CAS 75-28-5)

US. California Proposition 65

Not Listed.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	*	1
FLAMMABILITY		4
PHYSICAL HAZARD		1
PERSONAL PROTECTION		X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

25-May-2017

Version #

02

Effective date

19-July-2018

Prepared by

Falcon Safety Products, Inc. 908-707-4900

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.